



**HEXAGON**

# **Forced Response of Coupled Plate and Cavity**

Actran Student Edition Tutorial


## **Workshop description**

# Introduction

- This workshop demonstrates Actran capabilities to compute response of coupled plate / cavity system to mechanical excitation
- The objectives of this workshop are the following:
  - Compute the structural and cavity responses to a point load excitation on the plate
  - Get introduced to incongruent meshing technique for structure/cavity coupling
- Software version:
  - Actran 2021.1 Student Edition
- **Pre-requisites** - before going through this presentation, the reader should have read and understood the following presentation:
  - Workshops : Plate modes, plate forced response
  - Workshops: Cavity modes, cavity forced response

# Workshop description

- The plate has the same size, thickness and material as the one in the tutorials of “plate forced response” and “plate modes extraction”
- The air cavity has the same size as the one in tutorials “cavity forced response” and “cavity modes extraction”
- The excitation is modeled as an harmonic force applied on the plate



# Geometry description


- Let us consider a plate with the following properties:
  - Size:  $L_x = 0.75 \text{ m}$ ,  $L_y = 0.40 \text{ m}$ , thickness  $t = 0.003 \text{ m}$
  - Material properties:  $E = 7 \cdot 10^{10} \text{ Pa}$  with 1% damping,  $\nu = 0.25$  and  $\rho = 2400 \text{ kg/m}^3$
  - Plate simply supported along the four edges
  - Time-harmonic point load with unit amplitude at point  $x = 0.2 \text{ m}$ ,  $y = 0.1 \text{ m}$ :

$$F(t) = R(Ae^{i\omega t}) \text{ where } A = 1 \text{ and } \omega = 2\pi f$$


# **Workshop pre-processing**

# Start ActranVI

- Start ActranVI:
  - Shortcut is available through the Windows Start Menu



*(Windows Start Menu)*





# Set the working directory

Select the workshop input directory as the working directory

- The working directory is the project directory where all ActranVI related files are output






*The working directory path should not contain any space or special character*







# Import the analysis of “Plate force response”

- Import the *input\_plate\_forced.edat* analysis




# Create the cavity mesh (1)

- Create a structured mesh






- Visualize it before creation




## Create the cavity mesh (2)


- Extrude the structured mesh



- Visualize it before creation



# Create the cavity mesh



vp 1 (active)  
First Result

1

vp 1 (active)  
First Result

2

File Home **Mesh** Analysis Run Results Tools View Help

Import Recent Import New NFF BDF CAD Creation Edit Edge Surface Volume Transform Export All Meshes Export


Meshing Tools

3


Create All Domains Domains

# Create the cavity domain


- Rename the following domains
  - *Extrude\_volume* → *cavity\_volume*
  - *Structured\_mesh* → *cavity\_coupling\_surface*



2




# Create a Finite Fluid component for the cavity (1)




Add a *Finite Fluid* component

Set up the *Finite Fluid* component domain




## Create a Finite Fluid component for the cavity (2)



Define a material for air

- Add a Fluid Material
- Set the following properties:
  - $c = 340 + 0.17j \text{ m/s}$  (see next slide)
  - $\rho = 1.225 \text{ kg/m}^3$



Close both property windows (material & component)

# Internal losses in fluids (1)

- Air viscosity induces an exponential decrease of a wave's amplitude with distance
- The pressure distribution can be expressed as follows:

$$p = e^{-ikx} \cdot e^{-\alpha x} = e^{-i\tilde{k}x}$$

Where  $\alpha$  is the attenuation coefficient

- The attenuation effect can be analyzed as an addition of an imaginary part to the wave number which becomes complex:

$$\tilde{k} = k - i\alpha = \frac{\omega - i\alpha c}{c} = \frac{\omega}{c} \left( 1 - \frac{i\alpha c}{\omega} \right)$$

- Assuming

$$1 - \epsilon \simeq \frac{1}{1 + \epsilon} \text{ for } \epsilon \ll 1 \rightarrow \tilde{k} \simeq \frac{\omega}{c \left( 1 + i \frac{\alpha c}{\omega} \right)}$$



## Internal losses in fluids (2)

- This decrease can be carried by the speed of sound through the definition of a complex quantity:

$$\tilde{k} \simeq \frac{\omega}{\tilde{c}} \text{ with } \tilde{c} = c \left( 1 + i \frac{\alpha c}{\omega} \right) = c \left( 1 + i \frac{\alpha}{k} \right)$$


- The internal loss factor is the ratio between the imaginary part and the real part of the speed of sound. An internal loss of 0.05% leads to a speed of sound of  $(340+0.17j)$  m/s

$$\tilde{p}(x) = e^{i\tilde{k}x} = e^{-i\frac{\omega}{\tilde{c}}x} = e^{-ix\left(\frac{\omega}{c(1+i\frac{\alpha c}{\omega})}\right)} = e^{-ix\left(\frac{\omega-i\alpha c}{c}\right)} = e^{-ikx} \cdot e^{-\alpha x}$$

- For acoustic radiation in closed cavities, these viscous losses are often considered
- For exterior acoustic problem they have a very limited impact on results


# Plate – Cavity coupling

- The plate and the cavity overlap, but do not share the same nodes. In this case, an Interface Component needs to be created for the plate / cavity incompatible coupling
- An Interface links two Coupling Surfaces
  - **Surface 1**: the shell mesh (surface)
  - **Surface 2**: the surface mesh of the cavity which is in contact with the plate



# Plate – Cavity coupling – Incompatible mesh

- Using incompatible mesh, a pair of coupling surfaces needs to be defined to specify which parts of the mesh needs to be coupled
- To obtain the best projection
  - Coupling surface 1: with smallest elements
  - Coupling surface 2: with largest elements








# Plate – Cavity coupling – Interface



Add an *Interface*

Add the the plate mesh as Surface 1


Add the cavity coupling surface mesh as Surface 2




# Add cavity Field Points in the FRF output



If you are using Actran 2021 version



If you are using Actran 2021.1 version




Add a *Field Point* to define 2 microphones



Set up the *Field Point* coordinates explicitly

# Attach Field Points located on the plate to the Shell component

- With the cavity volume added to the model, the three field points on the plate need to be attached explicitly to the shell components to ensure these field points are considered as “accelerometers” on the plate and not as “microphones” in the cavity
- The field points inside the cavity do not need to be attached to the cavity as they are too far away from the plate to be “misplaced” and considered as “accelerometer” on the plate.




# Post-processing parameters – Maps



Add an *Output Map* post-processing parameter

Specify a map in \*.nff format to be saved in the whole mesh, at each frequency step



# Launch the Actran analysis in ActranVI



Launch the computation



Check the log showing the computation progress



Import the \*.plt computation result file






# **Post-processing in the PLTViewer**


# Evaluate the structural displacement

- The plate vibrates along the Z axis, the amplitude of structural displacement along the Z axis is **plot for each point**
- Visualize the plot using a logarithm scale for displacement amplitude



(For the 3 points in *POINT\_1*)



# Structural displacement at each Field Point in the plate



# Structural Displacement



## Comparison with Plate Forced Response Model

- Import the (provided) PLT results file *plate\_only\_forced\_response.plt* and compare the structural displacement between two models
- The plate response is slightly altered by the coupled cavity
- Several cavity eigen frequencies appear on the curve of the coupled problem (see workshop of cavity modes)




# Evaluate the cavity acoustic pressure

- Create a new figure
- Plot the pressure of the field point 1 and field point 2 of cavity in dB (SPL)



# Evaluate the cavity acoustic pressure




- More peaks in pressure can be observed for the point at coordinates [0.6, 0.3, 0.5]

# Evaluate the cavity acoustic pressure

- Different peaks on the FRF of cavity field points are due to different plate modes and cavity modes → see again the workshops of plates modes and cavity modes to find the eigen frequencies
- Take the cavity field point at [0.6, 0.3, 0.5] for example
- Peak frequencies [Hz]:

64	100	167	203	228	243	263	...
----	-----	-----	-----	-----	-----	-----	-----



Peaks due to plate mode






Peaks due to cavity mode

# Import the displacement results mesh

Go back to ActranVI

Load the output **map\_plate.nff** file containing the maps

Import the displacement results








# Import the pressure results mesh

Go back to ActranVI






Load the output **map\_cavity.nff** file containing the maps

Import the displacement results







# Visualize all results

- Visualize
  - Pressure map real part
  - Displacement map real part
  - Displacement deformation of the mesh




# Visualize all results

- Adjust visualization parameters
  - Set pressure results opacity to 0.5
  - Display different frequencies
  - Adapt the deformation factor consequently



# Visualize all results

Response driven by plate modes



Response driven by cavity modes

